


+

1/14

FIG 1: current frequency



$$f = c / (3 a) = \text{drive frequency in Hz}$$


$$p = \text{pulse duration} = T / 3, \text{ where } T = 1 / f$$

+

+

2/14

FIG 2: phasing chart



$$f = c / (3 a) = \text{drive frequency in Hz}$$


$$p = \text{pulse duration} = T / 3, \text{ where } T = 1 / f$$

+

+

3/14

FIG 3: x and z separation of 2 segments, ie segment pair




10036893 6632001

+

+


4/14

FIG 4: x and z separations of neighboring segments



+


FIG 5: x and y separations in a single plate



+

6/14

FIG 6: z and y separation in two plates




+

+

7/14

FIG 7: perspective view of the two plates




20250706 16:33:00



+

FIG 8: close-up perspective view of the two plates and current segments


Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km





9/14


FIG 9: m-n segment distance relationship



+

10/14

FIG 10: Force between current-carrying conducting wires



$I$  current in the wires

In this theoretical description, the values of  $a$ ,  $h_1$ ,  $h_2$ ,  $l_1$ ,  $l_2$  and  $I$  are variable



+

FIG 11: Plate 1 (0,0) to Plate 2 (m,n) segment distance, B






FIG 12: timing differences



+

FIG 13: Gazette view



Distance 'a' is fixed for a particular SCAM, but is flexible to support SCAMs of different scales. Typical values for 'a' would range from 1 cm to 1 km

+

14/14

FIG 14: Relativistic force between current-carrying conducting wires





FIG 15 Lorentz length contraction



+